

RAM OIL 500 TMP





Depureco Industrial Vacuums USA

19121 Marketplace Avenue, Building 1, Suite 165
Plum Creek Business Park • Kyle • TX 78640


www.depurecousa.com
info@depurecousa.com

 Power: 4 HP

 Liquid capacity: 134 gal
Solid capacity: 18 gal

 Sucking time: 74 gal/min
Dumping time: 74 gal/min



Available with powerful
6.5 HP side channel blower
Max Airflow= 210 CFM
Max depression= 125 inH2O



Tilttable hopper with
metal swarf collecting grid.
18 gal capacity
PPL Filter (150 μ)



3 By-Pass motors
120V/60 Hz
Max Airflow = 345 CFM
Max Depression = 94 inH2O



Handy accessory
basket




Oil proof cartridge for
oil mist



134 gal capacity

PUMP: Discharging pump
Speed discharge system 74 gal/min

Pivoting Ø 7.7 in
sturdy wheels



Stainless steel AISI 316
inspection door

SPEC SHEET

	Units	RAM OIL 500 TMP	RAM OIL 500 T
Motors Type		3 - By-Pass	Side channel blower
Power	HP	4	6.5
Voltage Frequency	V/Hz	120/60	480/60
Maximum vacuum	inH2O	94	125
Maximum air flow	CFM	345	210
Inlet	Ø in	2	2
Noise level - (EN ISO 3744)	dB(A)	72	72
Liquid capacity	gal	134	134
Solid capacity	gal	18	18
Dimensions	in	24 x 65	24 x 65
Hight	In	70	70
Weight	lb	705	705
Suction time	gal/min	74	74
Dumping time	gal/min	74	74
Discharge system			
Type		External pump	External pump
Power	HP	1	1
Voltage/Frequency	V/Hz	1 10/60	1 10/60

INCLUDED



**PPL disposal filter 150
µ efficiency**



TNT filter



Oil & swarf KIT

ACCESSORIES



Oil & swarf KIT PRO