



ECOBU

Depureco Industrial Vacuums USA

19121 Marketplace Avenue, Building 1, Suite 165
Plum Creek Business Park • Kyle • TX 78640

www.depurecousa.com
info@depurecousa.com

4.6 HP
POWER

3800 in²
FILTER

26 gal Bin
CAPACITY

**POWERFUL
SIDE CHANNEL BLOWER**
480V
Max Airflow= 247 CFM
Max Depression= 115 inH2O



M CLASS
Stellar filter



MTF OPTIONAL
For difficult and sticky dust.




3,800 in²



**STANDARD H 14
HEPA FILTER**



4,400 in²



**MANUAL SHAKER
CLEANING SYSTEM**

Smart handle for shaking
the filter aggressively to
release dust.


**OPTIONAL
TANGENTIAL
INLET**



26 gal

**DETACHABLE BIN
ON WHEELS**

**INLET WITH
DEFLECTOR**



**WET & DRY FIXED BRUSH
FLOOR TOOL**



**TILTABLE KIT FOR DUSTING
BIN**




SPEC SHEET

	Units	ECOBULL
Motors Type		Side channel blower
Power	HP	4.63
Voltage Frequency	V Hz	480/60
Maximum vacuum	inH2O	119
Maximum air flow	CFM	247
Inlet	Ø in	2.75
Noise level - (EN ISO 3744)	dB(A)	72
Bin capacity	gal	26
Dimensions	in	25.98 X 31.50
Height	in	59.65
Weight	lb	194
Primary filter		
Type		Star filter
Surface area Diameter	in² in	3,800
(Class EN 60335-2-69)		M Class
Media		Polyester
Filter cleaning		Manual Shaker
Absolute filter		
Surface area	in²	4,400
(Class - EN 1822)		H14
Media		Fiberglass

OPTIONAL FILTERS



BFL
M class filter 409028,6 ft²



ANT M
Antistatic filter



MTF
Teflon filter



NOMEX
482° F Resistant filter



PTFE
PTFE filter 409028,6 ft²

OPTIONAL



AB
Accessory basket



GRD
Grounding



TAN
Tangential inlet + cyclone



BX
AISI 304 stainless stell bin



GX
AISI 304 BIN AND CHAMBER



FLT
Floating device for liquids

ACCESSORIES



Iron reducer
Ø 2.75 / 2 in



Wet & Dry Kit
Ø 2 in



Starter Kit
Ø 2 in