

PUMA



Depureco Industrial Vacuums USA

19121 Marketplace Avenue, Building 1, Suite 165
Plum Creek Business Park • Kyle • TX 78640

www.depurecousa.com
info@depurecousa.com

11.5 to
28.6 HP

POWER

7000 in²

FILTER

46 gal Bin

CAPACITY



**MANUAL SHAKER
CLEANING SYSTEM**

Smart handle for shaking
the filter aggressively to
release dust.

**POWERFUL
SIDE CHANNEL BLOWER**
480V/60 Hz



M CLASS
Stellar filter




MTF OPTIONAL
For difficult and
sticky dust.



5900 in²

**TANGENTIAL
INLET WITH
CYCLON**



46 gal

**DETACHABLE BIN
ON WHEELS**


SPEC SHEET

	Units	PUMA 10	PUMA 15 P	PUMA 15 S	PUMA 18 P	PUMA 20	PUMA 25
Motors Type		Side channel blower	Side channel blower	Side channel blower	Side channel blower	Side channel blower	Side channel blower
Power	HP	11.5	17.5	23.2	16.9	23.2	28.8
Voltage Frequency	V Hz	480/60	480/60	480/60	480/60	480/60	480/60
Maximum vacuum	inH2O	120	120	220	110	140	148
Maximum air flow	CFM	490	660	364	520	660	940
Inlet	Ø in	4	4	4	4	4	4
Noise level - (EN ISO 3744)	dB(A)	74	74	74	74	74	74
Bin capacity	gal	46	46	46	46	46	46
Dimensions	in	33.46 X 61.02	33.46 X 61.02	33.46 X 61.02	33.46 X 61.02	33.46 X 61.02	33.46 X 61.02
Height	in	77.95	77.95	77.95	77.95	77.95	77.95
Weight	lb	650	595	800	783	639	816
Primary filter							
Type		Star filter	Star filter	Star filter	Star filter	Star filter	Star filter
Surface area Diameter	in² in	7000	7000	7000	7000	7000	7000
(Class EN 60335-2-69)		M Class	M Class	M Class	M Class	M Class	M Class
Media		Polyester	Polyester	Polyester	Polyester	Polyester	Polyester
Filter cleaning		Manual Shaker	Manual Shaker	Manual Shaker	Manual Shaker	Manual Shaker	Manual Shaker

OPTIONAL FILTERS



BFL
M class filter 409028,6 ft²



ANT M
Antistatic filter



MTF
Teflon filter



NOMEX
482° F Resistant filter



PTFE
PTFE filter 409028,6 ft²

OPTIONAL



GRD
Grounding



TAN
Tangential inlet + cyclone



BX
AISI 304 stainless stell bin



GX
AISI 304 BIN AND CHAMBER



FLT
Floating device for liquids

ACCESSORIES



Iron reducer
Ø 2.75 / 2 in



Wet & Dry Kit
Ø 2 in



Starter Kit
Ø 2 in