

TX



Depureco Industrial Vacuums USA

19121 Marketplace Avenue, Building 1, Suite 165
Plum Creek Business Park • Kyle • TX 78640

www.depurecousa.com
info@depurecousa.com



4.8 to
11.5 HP
POWER

5900 in²
FILTER

26 gal Bin
CAPACITY

**POWERFUL
SIDE CHANNEL BLOWER**
480V/60 Hz



M CLASS
Stellar filter




MTF OPTIONAL
For difficult and
sticky dust.




5900 in²

**OPTIONAL
TANGENTIAL
INLET**




**INLET WITH
DEFLECTOR**



**MANUAL SHAKER
CLEANING SYSTEM**

Smart handle for shaking
the filter aggressively to
release dust.



26 gal

**DETACHABLE BIN
ON WHEELS**




SPEC SHEET

	Units	TX 300	TX 400P	TX 400S	TX 550P	TX 550S	TX 750
Motors Type		Side channel blower	Side channel blower	Side channel blower	Side channel blower	Side channel blower	Side channel blower
Power	HP	4.8	6.5	6.5	8.5	8.5	11.5
Voltage Frequency	V Hz	480/60	480/60	480/60	480/60	480/60	480/60
Maximum vacuum	inH2O	119	100	125	100	177	145
Maximum air flow	CFM	247	300	210	400	210	400
Inlet	Ø in	2.75	2.75	2.75	2.75	2.75	2.75
Noise level - (EN ISO 3744)	dB(A)	74	76	76	76	76	79
Bin capacity	gal	26	26	26	26	26	26
Dimensions	in	25.59 X 43.31	25.59 X 43.31	25.59 X 43.31	25.59 X 43.31	25.59 X 43.31	25.59 X 43.31
Height	in	55.12	55.12	55.12	55.12	55.12	55.12
Weight	lb	287	309	309	345	345	419
Primary filter							
Type		Star filter	Star filter	Star filter	Star filter	Star filter	Star filter
Surface area Diameter	in² in	5900	5900	5900	5900	5900	5900
(Class EN 60335-2-69)		M Class	M Class	M Class	M Class	M Class	M Class
Media		Polyester	Polyester	Polyester	Polyester	Polyester	Polyester
Filter cleaning		Manual Shaker	Manual Shaker	Manual Shaker	Manual Shaker	Manual Shaker	Manual Shaker

OPTIONAL FILTERS



BFL
M class filter 409028,6 ft²



ANT M
Antistatic filter



MTF
Teflon filter



NOMEX
482° F Resistant filter



PTFE
PTFE filter 409028,6 ft²

OPTIONAL



GRD
Grounding



TAN
Tangential inlet + cyclone



BX
AISI 304 stainless steel bin



GX
AISI 304 BIN AND CHAMBER



FLT
Floating device for liquids

ACCESSORIES



Iron reducer
Ø 2.75 / 2 in



Wet & Dry Kit
Ø 2 in



Starter Kit
Ø 2 in